MC14503B

Hex Non-Inverting 3-State Buffer

The MC14503B is a hex non−inverting buffer with 3−state outputs, and a high current source and sink capability. The 3−state outputs make it useful in common bussing applications. Two disable controls are provided. A high level on the Disable A input causes the outputs of buffers 1 through 4 to go into a high impedance state and a high level on the Disable B input causes the outputs of buffers 5 and 6 to go into a high impedance state.

Features

- 3−State Outputs
- TTL Compatible − Will Drive One TTL Load Over Full Temperature Range
- Supply Voltage Range = 3.0 Vdc to 18 Vdc
- Two Disable Controls for Added Versatility
- Pin for Pin Replacement for MM80C97 and 340097
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q100 Qualified and PPAP Capable
- This Device is Pb−Free and is RoHS Compliant

MAXIMUM RATINGS (Voltages Referenced to V_{SS}) (Note 1)

Parameter	Symbol	Value	Unit
DC Supply Voltage Range	V_{DD}	−0.5 to +18.0	V
Input or Output Voltage Range (DC or Transient)	V_{in}, V_{out}	−0.5 to V_{DD} + 0.5	V
Input Current (DC or Transient) per Pin	I_{in}	±10	mA
Output Current (DC or Transient) per Pin	I_{out}	±25	mA
Power Dissipation, per Package (Note 2)	P_D	500	mW
Ambient Temperature Range	T_A	−55 to +125	°C
Storage Temperature Range		−65 to +150	°C
Lead Temperature (8−Second Soldering)		260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. Maximum Ratings are those values beyond which damage to the device may occur.
2. Temperature Derating:
   "D/DW" Package: –7.0 mW/°C From 65°C To 125°C

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high−impedance circuit. For proper operation, V_{in} and V_{out} should be constrained to the range $V_{SS} \le (V_{in}$ or $V_{out}) \le V_{DD}$.

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either V_{SS} or V_{DD}). Unused outputs must be left open.

ON Semiconductor®


http://onsemi.com



1

SOIC−16
D SUFFIX
CASE 751B

PIN ASSIGNMENT



MARKING DIAGRAM



A = Assembly Location
WL, L = Wafer Lot
YY, Y = Year
WW, W = Work Week
G = Pb−Free Package

TRUTH TABLE

In_n	Appropriate Disable Input	Out_n
0	0	0
1	0	1
X	1	High Impedance


X = Don't Care

ORDERING INFORMATION


See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

© Semiconductor Components Industries, LLC, 2014

LOGIC DIAGRAM



CIRCUIT DIAGRAM



*Diode protection on all inputs (not shown)

ELECTRICAL CHARACTERISTICS (Voltages Referenced to V_{SS})

Characteristic	Symbol	V_{DD} Vdc	−55°C Min	−55°C Max	25°C Min	25°C Typ (Note 3)	25°C Max	125°C Min	125°C Max	Unit
Output Voltage “0” Level V_{in} = 0	V_{OL}	5.0	–	0.05	–	0	0.05	–	0.05	Vdc
		10	–	0.05	–	0	0.05	–	0.05	
		15	–	0.05	–	0	0.05	–	0.05	
“1” Level V_{in} = V_{DD}	V_{OH}	5.0	4.95	–	4.95	5.0	–	4.95	–	Vdc
		10	9.95	–	9.95	10	–	9.95	–	
		15	14.95	–	14.95	15	–	14.95	–	
Input Voltage “0” Level	V_{IL}									Vdc
(V_O = 3.6 or 1.4 Vdc)		5.0	–	1.5	–	2.25	1.5	–	1.5	
(V_O = 7.2 or 2.8 Vdc)		10	–	3.0	–	4.50	3.0	–	3.0	
(V_O = 11.5 or 3.5 Vdc)		15	–	4.0	–	6.75	4.0	–	4.0	
“1” Level	V_{IH}									Vdc
(V_O = 1.4 or 3.6 Vdc)		5.0	3.5	–	3.5	2.75	–	3.5	–	
(V_O = 2.8 or 7.2 Vdc)		10	7.0	–	7.0	5.50	–	7.0	–	
(V_O = 3.5 or 11.5 Vdc)		15	11	–	11	8.25	–	11	–	
Output Drive Current	I_{OH}									mAdc
(V_{OH} = 2.5 Vdc) Source		4.5	–4.3	–	–3.6	–5.0	–	–2.5	–	
(V_{OH} = 2.5 Vdc)		5.0	–5.8	–	–4.8	–6.1	–	–3.0	–	
(V_{OH} = 4.6 Vdc)		5.0	–1.2	–	–1.02	–1.4	–	–0.7	–	
(V_{OH} = 9.5 Vdc)		10	–3.1	–	–2.6	–3.7	–	–1.8	–	
(V_{OH} = 13.5 Vdc)		15	–8.2	–	–6.8	–14.1	–	–4.8	–	
(V_{OL} = 0.4 Vdc) Sink	I_{OL}	4.5	2.2	–	1.8	2.1	–	1.2	–	mAdc
(V_{OL} = 0.4 Vdc)		5.0	2.6	–	2.1	2.3	–	1.3	–	
(V_{OL} = 0.5 Vdc)		10	6.5	–	5.5	6.2	–	3.8	–	
(V_{OL} = 1.5 Vdc)		15	19.2	–	16.1	25	–	11.2	–	
Input Current	I_{in}	15	–	±0.1	–	±0.00001	±0.1	–	±1.0	μAdc
Input Capacitance, (V_{in} = 0)	C_{in}	–	–	–	–	5.0	7.5	–	–	pF
Quiescent Current, (Per Package)	I_Q	5.0	–	1.0	–	0.002	1.0	–	30	μAdc
		10	–	2.0	–	0.004	2.0	–	60	
		15	–	4.0	–	0.006	4.0	–	120	
Total Supply Current (Note 4, 5) (Dynamic plus Quiescent, Per Package) (C_L = 50 pF on all outputs) (All outputs switching, 50% Duty Cycle)	I_T	5.0	I_T = (2.5 μA/kHz) f + I_{DD}							μAdc
		10	I_T = (6.0 μA/kHz) f + I_{DD}							
		15	I_T = (10 μA/kHz) f + I_{DD}							
3−State Output Leakage Current	I_{TL}	15	–	±0.1	–	±0.0001	±0.1	–	±3.0	μAdc

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Data labelled “Typ” is not to be used for design purposes but is intended as an indication of the IC’s potential performance.
4. The formulas given are for the typical characteristics only at 25°C.
5. To calculate total supply current at loads other than 50 pF: $I_T(C_L) = I_T(50\ pF) + (C_L - 50)$ Vfk where: I_T is in μA (per package), C_L in pF, V = ($V_{DD} - V_{SS}$) in volts, f in kHz is input frequency, and k = 0.006.

SWITCHING CHARACTERISTICS (Note 6) (C_L = 50 pF, T_A = 25°C)

Characteristic	Symbol	V_{DD} V_{CC}	All Types		Unit
			Typ (Note 7)	Max	
Output Rise Time	t_{TLH}				ns
t_{TLH} = (0.5 ns/pF) C_L + 20 ns		5.0	45	90	
t_{TLH} = (0.3 ns/pF) C_L + 8.0 ns		10	23	45	
t_{TLH} = (0.2 ns/pF) C_L + 8.0 ns		15	18	35	
Output Fall Time	t_{THL}				ns
t_{THL} = (0.5 ns/pF) C_L + 20 ns		5.0	45	90	
t_{THL} = (0.3 ns/pF) C_L + 8.0 ns		10	23	45	
t_{THL} = (0.2 ns/pF) C_L + 8.0 ns		15	18	35	
Turn−Off Delay Time, all Outputs	t_{PLH}				ns
t_{PLH} = (0.3 ns/pF) C_L + 60 ns		5.0	75	150	
t_{PLH} = (0.15 ns/pF) C_L + 27 ns		10	35	70	
t_{PLH} = (0.1 ns/pF) C_L + 20 ns		15	25	50	
Turn−On Delay Time, all Outputs	t_{PHL}				ns
t_{PHL} = (0.3 ns/pF) C_L + 60 ns		5.0	75	150	
t_{PHL} = (0.15 ns/pF) C_L + 27 ns		10	35	70	
t_{PHL} = (0.1 ns/pF) C_L + 20 ns		15	25	50	
3−State Propagation Delay Time	t_{PHZ}	5.0	75	150	ns
Output “1” to High Impedance		10	40	80	
		15	35	70	
Output “0” to High Impedance	t_{PLZ}	5.0	80	160	ns
		10	40	80	
		15	35	70	
High Impedance to “1” Level	t_{PZH}	5.0	65	130	ns
		10	25	50	
		15	20	40	
High Impedance to “0” Level	t_{PZL}	5.0	100	200	ns
		10	35	70	
		15	25	50	

6. The formulas given are for the typical characteristics only at 25°C.
7. Data labelled “Typ” is not to be used for design purposes but is intended as an indication of the IC’s potential performance.




Figure 1. Switching Time Test Circuit and Waveforms (t_{TLH}, t_{THL}, t_{PHL}, and t_{PLH})




Figure 2. 3−State AC Test Circuit and Waveforms (t_{PLZ}, t_{PHZ}, t_{PZH}, t_{PZL})

ORDERING INFORMATION


Device	Package	Shipping†
MC14503BDG	SOIC−16 (Pb−Free)	48 / Rail
MC14503BDR2G	SOIC−16 (Pb−Free)	2500 / Tape & Reel
NLV14503BDR2G*	SOIC−16 (Pb−Free)	2500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q100 Qualified and PPAP Capable.

PACKAGE DIMENSIONS


SOIC−16
CASE 751B−05
ISSUE K



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	9.80	10.00	0.386	0.393
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

SOLDERING FOOTPRINT



DIMENSIONS: MILLIMETERS

ON Semiconductor and the ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative