
JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

TO-220-3L Plastic-Encapsulate Voltage Regulators

CJ7812 Three-terminal positive voltage regulator

FEATURES

- Maximum output current
  I_{OM}: 1.5 A
- Output voltage
  V_O: 12 V
- Continuous total dissipation
  P_D: 1.25 W (T_a= 25 ℃)



ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)


Parameter	Symbol	Value	Unit
Input Voltage	V_i	35	V
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	80	℃/W
Operating Junction Temperature Range	T_{OPR}	-40~+125	℃
Storage Temperature Range	T_{STG}	-65~+150	℃

ELECTRICALCHARACTERISTICS AT SPECIFIED VIRTUAL JINCTION TEMPERATURE (Vi=19V, Io=500mA, Ci=0.33μF, Co=0.1μF, unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output Voltage	Vo	T_J=25℃	11.64	12.0	12.36	V
		Io= 5mA-1A, 14.5V≤ V_i ≤27V	11.4	12.0	12.6	V
Load Regulation	ΔVo	I_O=5mA -1.5A ,T_J=25℃		10	240	mV
		I_O=250mA - 750mA		3	120	mV
Line Regulation	ΔVo	14.5V≤ Vi ≤30V ,T_J=25℃		12	240	mV
		16V≤V ≤22V ,T_J=25℃		4	120	mV
Quiescent Current	Iq	T_J=25℃		4.3	8	mA
Quiescent Current Change	ΔIq	5.0mA≤ I_O ≤1.0A			0.5	mA
		14.5V ≤V_i≤ 30V			1.0	mA
Output Voltage Drift	△Vo/△T	I_O=5mA		-1		mV/℃
Output Noise Voltage	V_N	f =10Hz to 100KHz ,T_J=25℃		75		μV/Vo
Ripple Rejection	RR	f =120Hz, 15V≤ V_i ≤25V	55	71		dB
Dropout Voltage	V_d	I_O=1.0A ,T_J=25℃		2		V
Output Resistance	R_O	f = 1KHz		18		mΩ
Short Circuit Current	Isc	T_J=25℃		350		mA
Peak Current	Ipk	T_J=25℃		2.2		A

* Pulse test.


TYPICAL APPLICATION




Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

Typical Characteristics


Output Characteristics




Dropout Characteristics




Quiescent Current vs Input Voltage




Current Cut-off Grid Voltage




Output Voltage vs Junction Temperature



Power Derating Curve



TO-220-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.470	4.670	0.176	0.184
A1	2.520	2.820	0.099	0.111
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.310	0.530	0.012	0.021
c1	1.170	1.370	0.046	0.054
D	10.010	10.310	0.394	0.406
E	8.500	8.900	0.335	0.350
E1	12.060	12.460	0.475	0.491
e	2.540 TYP		0.100 TYP	
e1	4.980	5.180	0.196	0.204
F	2.590	2.890	0.102	0.114
h	0.000	0.300	0.000	0.012
L	13.400	13.800	0.528	0.543
L1	3.560	3.960	0.140	0.156
Φ	3.735	3.935	0.147	0.155

DISCLAIMER

IMPORTANT NOTICE, PLEASE READ CAREFULLY

The information in this data sheet is intended to describe the operation and characteristics of our products. JSCJ has the right to make any modification, enhancement, improvement, correction or other changes to any content in this data sheet, including but not limited to specification parameters, circuit design and application information, without prior notice.

Any person who purchases or uses JSCJ products for design shall: 1. Select products suitable for circuit application and design; 2. Design, verify and test the rationality of circuit design; 3. Procedures to ensure that the design complies with relevant laws and regulations and the requirements of such laws and regulations. JSCJ makes no warranty or representation as to the accuracy or completeness of the information contained in this data sheet and assumes no responsibility for the application or use of any of the products described in this data sheet.

Without the written consent of JSCJ, this product shall not be used in occasions requiring high quality or high reliability, including but not limited to the following occasions: medical equipment, automotive electronics, military facilities and aerospace. JSCJ shall not be responsible for casualties or property losses caused by abnormal use or application of this product.

Official Website: www.jscj-elec.com

Copyright © JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.